

Sport Parachute RL-16/3

SPEKON[®]
made in Germany since 1842

IDEAL CANOPY FOR ACCURACY AND DEMO'S

The **RL-16/3** has been developed in close cooperation with competitive athletes especially for accuracy landings.

The canopy **RL-16/3** is characterized by high steering precision and course stability.

The short steering distances and the special aerodynamics of this canopy make most accurate and quick steering corrections possible, even in strongly braked mode shortly before landing.

The canopy **RL-16/3** is manufactured by SPEKON GmbH in accordance with German standards and holds a German approval.

With the **RL-16/3** canopy won already many jumpers the world championship in accuracy and precision.

This canopy is available in sizes **230, 250, 270, 280** and **300** sqft.

Nato-Stock-No.: 1670-12-371-0992

TECHNICAL PARAMETER	P/N: 50-382/04	P/N: 50-382/07	P/N: 50-382/02	P/N: 50-382/03	P/N: 50-382/06
Parachute canopy area	230 sqft	250 sqft	270 sqft	280 sqft	300 sqft
Weight approx.	5,1 – 6,0 kg				
Number of cells	7	7	7	7	7
Canopy fabric	low porosity	low porosity	low porosity	low porosity	low porosity
Volumen of the packed parachute approx.	700 inch ³	740 inch ³	790 inch ³	820 inch ³	900 inch ³
Min. / Max. payload on the parachute	40 / 90 kg	50 / 100 kg	60 / 120 kg	70 / 140 kg	80 / 160 kg
Max. exit velocity	240 km/h (130 KEAS)				
Min. exit altitude	600 m for aircraft with launch speed of \geq 60 KEAS 700 m for aircraft with launch speed of 0 KEAS				
Rate of descent	approx. 3 – 5 m/s, max. 7 m/s* (*depends on weight and steering position)				
Special feature	very precise landings				
Max. packing time	180 days				
Service lifetime period	unlimited (yearly verification by rigger is obligated)				



www.spekons.com

Safe to the Target –
with SPEKON Parachutes.

CONTACT
Fon: +49 3586 456-0
Fax: +49 3586 456-167
Mail: info@spekon.de

SPEKON
Sächsische Spezialkonfektion GmbH
Nordstraße 40
D-02782 Seifhennersdorf / GERMANY